

## TITLE OF THE INVENTION

## FLUID CONTROL DEVICE

## BACKGROUND OF THE INVENTION

The present invention relates to fluid control  
5 devices for use in semiconductor manufacturing apparatus, and more particularly to integrated fluid control devices from which fluid controllers are removable upward for maintenance or inspection.

Throughout the specification and the appended  
10 claims, the term "front" refers to the right-hand side of FIGS. 1 and 4, the term "rear" to the left-hand side of these drawings, and the terms "upper" and "lower" respectively to the upper and lower sides of the drawings. The terms "left" and "right" are used for the  
15 device as it is seen from the front rearward. Such terms are used for convenience sake; the device may be used as reversed with respect to the longitudinal direction, or as laid on its side.

Fluid control devices for use in semiconductor  
20 manufacturing apparatus comprise various fluid controllers arranged in rows, with the fluid channels of fluid controllers in adjacent lines interconnected by connect-

5

10

## SUMMARY OF THE INVENTION

An object of the present invention is to provide a fluid control device which is easy to assemble and which

is readily adapted for the additional installation or modification of lines.

As a first feature of the present invention, the invention provides a fluid control device wherein a plurality of lines each comprise a plurality of fluid controllers arranged at an upper level and a plurality of coupling members arranged at a lower level, the plurality of lines being arranged in parallel on a base member and having inlets directed in the same direction, with outlets thereof facing toward the same direction, the fluid control device being characterized in that each line is mounted on a line support member, the line support member being mounted on the base member and slidable in a direction orthogonal to the line.

The fluid control device embodying the first feature of the invention can be assembled by attaching each line support member having coupling members and fluid controllers mounted thereon to a base member, and is therefore easy to assemble. Lines can be modified by removing channel connecting means upward as required, then removing the old line to be modified as mounted on the line support member, slidably moving the line support members of the lines not to be modified when so required, mounting on the base member the line support

member of the line to be substituted, further slidingly returning the line support members of the lines not to be modified to the proper position, and finally installing channel means as required for modification.

- 5 Similarly, lines can be additionally installed by removing channel connecting means upward as required, slidingly moving the line support members of the existing lines as required, mounting on the base member the line support member of the line to be added, further  
10 slidingly returning the line support members of the existing lines to the proper position, and finally installing channel means as required for addition. Thus, lines can be added or modified easily.

- Usable as the line support member is, for example, a  
15 plate member elongated longitudinally of the line. When required, a bent portion is provided at each end of the member so that the plate member can be mounted on the base member with ease. The line support member to be used may be any of rails shaped variously. Preferably  
20 in this case, the line support member is a rail removably mounted on the base member, and the coupling members are slidably mounted on the rail, each of the fluid controllers being mounted on two of the coupling members. When the coupling members and fluid

controllers are to be attached to the line support member in this case, the coupling members are slidably moved along rail to the required position, and each fluid controller is then mounted on two of the coupling members. Each line is thus easy to assemble. Furthermore, the fluid controller can be replaced by one having a different length by removing the fluid controller to be replaced, moving the coupling member along the rail to the required position, fixing the coupling member to the rail, and mounting the substitute fluid controller on the coupling members concerned. Similarly, additional fluid controllers and coupling members can be installed in the existing line. In this way, lines can be modified or additionally installed with ease.

According to the first feature of the invention, the rail is, for example, U-shaped in cross section and has inward flanges, and a slide member having an internally threaded portion is connected to the coupling member with a screw member. For example, the slide member having the internally threaded portion is inserted into the rail, and a screw member extending through the coupling member is screwed into the slide member, whereby the upper surface of the slide member is pressed

against the inward flanges of the rail from below,  
whereby the coupling member is attached to the rail.

As a second feature of the present invention, the  
invention provides a fluid control device wherein a  
5 plurality of lines each comprise a plurality of fluid  
controllers arranged at an upper level and a plurality  
of coupling members arranged at a lower level, the  
plurality of lines being arranged in parallel on a base  
member and having inlets directed in the same direction,  
10 with outlets thereof facing toward the same direction,  
the fluid control device being characterized in that the  
base member is provided with tracks arranged in parallel  
and corresponding to the respective lines, the coupling  
members being slidably mounted on the corresponding  
15 track, each of the fluid controllers being mounted on  
two of the coupling members.

According to the second feature of the invention,  
the fluid control device can be assembled by slidably  
moving the coupling members along the track to the  
20 required position, and thereafter mounting each of the  
fluid controller on the corresponding pair of these  
coupling members. Thus, the device is easy to assemble.

Furthermore, the fluid controller can be replaced by  
one having a different length by removing the fluid

100290-2258360

5 concerned. Similarly, additional fluid controllers and coupling members can be installed in the existing line. In this way, lines can be modified or additionally installed with ease.

10    respective coupling members are provided on the track,  
and each of the slide members is connected to the  
corresponding coupling member. The track and the slide  
member can be modified variously insofar as the slide  
member is slidable along the track and will not readily  
15    slip off from the track. For example, the track may be  
provided by a rail removably mounted on the base member,  
or the track may be provided by a groove in the upper  
surface of the base member. The former is more  
preferable.

20        When the tracks are provided by removable rails, the device can be assembled in its entirety by mounting on the base member the individual rails each having coupling members and fluid controllers mounted thereon. The device is therefore easy to assemble. Lines can be

modified merely by removing channel connecting means upward as required, removing the old line to be modified as mounted on the rail, mounting the rail of the substitute line on the base member, and finally

5 installing channel connecting means as required for modification. Similarly, lines can be added merely by removing channel connecting means upward as required, thereafter mounting on the base member the rail of the line to be added, and finally installing channel

10 connecting means as required for the additional installation. Thus, lines can be added or modified easily.

According to the second feature of the invention, the rail for providing the line support member or track

15 may be U-shaped in cross section and have inward flanges, or may be U-shaped in cross section and provided with outward flanges. Alternatively, the rail may be U-shaped in cross section and provided with a T-shaped intermediate wall dividing the rail widthwise

20 thereof. Preferably, the groove may have a downwardly enlarged trapezoidal cross section or an inverted T-shaped cross section.

The slide member may be attached to the rail with a screw member or provided with rail holding claws



engageable with the rail.

For example, the rail is U-shaped in cross section and has inward flanges, and a slide member having an internally threaded portion is connected to the coupling member with a screw member. For example, the slide member having the internally threaded portion is inserted in the rail, and a screw member extending through the coupling member is screwed in the slide member, whereby the upper surface of the slide member is pressed against the inward flanges from below to attach the coupling member to the rail. When the track is provided by a groove instead of the rail, an edge portion defining the opening of the groove is preferably provided with a portion for preventing the slide member from slipping off upward. The slipping-off preventing portion is readily available by shaping the groove in a downwardly enlarged trapezoidal form or inverted T-shaped form. In the case where the track is either a rail or groove, a clearance is preferably formed between each adjacent pair of fluid controllers for inserting therethrough a tool for rotating the screw.

The rail is U-shaped in cross section and has outward flanges, and the slide member is provided with rail holding claws engageable with the respective

outward flanges of the rail. Alternatively, the rail is U-shaped in cross section and has inward flanges, and the slide member is provided with rail holding claws engageable with the respective inward flanges of the rail. Preferably, the slide member provided with the rail holding claws is provided, for example, with an internally threaded portion, connected to the coupling member with a screw member and further fixed as positioned in place to the rail.

10 Preferably, the adjacent rails are connected to one another at a required position. This eliminates variations in the spacing between the rails, prevents the rails from backlashing and renders the device as assembled easy to use.

15 According to the first and second features of the invention, the base member is shaped in the form of a frame by an inlet-side rail, an outlet-side rail and connecting members interconnecting the side rails, using rails for providing line support members or tracks.

20 Rails may also be used as the connecting members in this case.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevation showing a first embodiment of fluid control device of the invention;

100290-2256860

FIG. 2 is a plan view of the same;

FIG. 3 is a view in section taken along the line  
III-III in FIG. 1;

FIG. 4 is a fragmentary view in section showing a  
5 second embodiment of fluid control device of the  
invention;

FIG. 5 includes fragmentary views in section showing  
third embodiments of fluid control device of the  
invention;

10 FIG. 6 is a side elevation showing a fourth  
embodiment of fluid control device of the invention;

FIG. 7 is a plan view of the same;

FIG. 8 is a view in section taken along the line  
VIII-VIII in FIG. 6;

15 FIG. 9 is a fragmentary view in section showing a  
fifth embodiment of fluid control device of the  
invention;

FIG. 10 is a fragmentary view in section showing a  
sixth embodiment of fluid control device of the  
20 invention;

FIG. 11 is a side elevation showing a seventh  
embodiment of fluid control device of the invention;

FIG. 12 is a plan view of the same;

FIG. 13 is a view in section taken along the line

105230-00000000

FIG. 14 is an enlarged view in horizontal section taken along the upper surface of a rail in FIG. 13;

FIG. 16 is an enlarged view in section taken along the upper surface of a rail in FIG. 15;

10        FIG. 18 includes a view in section showing a tenth  
embodiment of fluid control device of the invention; and

15 DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1 to 3 show a first embodiment of fluid control device of the invention. The device comprises a first line A, second line B and spare line C which are arranged in parallel on a base member 1 in the form of a plate.

The first line A and the second line B comprise fluid controllers 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12,



(at the inlet side) of the massflow controller 2, i.e., inlet first on-off valve 3, inlet second on-off valve 4, check valve 5, and lateral communication channel block 6, and the components provided in the rear (at the 5 outlet side) of the massflow controller 2, i.e., outlet first on-off valve 11, outlet second on-off valve 12, check valve 13 and branching-confluence through channel block 14.

The massflow controller 2 has an inlet connecting 10 portion 2a and an outlet connecting portion 2b respectively at the front and rear sides of its lower end portion. The massflow controller 2 is held in communication with the inlet first on-off valve 3 and the outlet first on-off valve 11 by a block couplings 21 15 having a V-shaped channel and disposed under these respective valves. The other adjacent fluid controllers 4, 6, 7, 8, 9, 10, 12, 14 are held in communication with one another by like block couplings 21 having a V-shaped channel. The manual valve 10 positioned at the inlet 20 end of the line A and the branching-confluence through channel block 14 at the outlet end of each of the lines A, B are each provided with a coupling 22 for connection to an external member.

The rail 20 has a through hole in each of its front

and rear ends and is fastened to the base member 1 by a screw 23 inserted through the hole. The block couplings 21 and the external member connecting couplings 22 have vertical internally threaded portions formed in their upper walls. Each of the fluid controllers 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 is attached to the coupling 21 or 22 by driving a screw 15 inserted through the controller into the internally threaded portion of the coupling 21 or 22.

10 With reference to FIG. 3, the rail 20 is U-shaped in cross section, and has outward flanges 20a and inward flanges 20b. The rail 20 has a slide member 24 inserted therein. The slide member 24 is made of metal and divided in two, i.e., into left and right half segments 15 24a, 24b, so as to be insertable into the rail 20 from above. Screws 26 extending through couplings 21 or 22 are screwed in vertical internally threaded portions 25 extending through the half segments 24a, 24b. A stepped portion is formed in the upper surface of each of the 20 half segments 24a, 24b so as to form a lower portion at the outer side thereof. The vertical threaded portion 25 is formed in the lower portion of each half segment. The slide member 24 is slidable with the screw 26 loosely screwed in the internally threaded portion 25

but is nonrotatable. When the screw 26 is tightened up in this state, the slide member 24 is moved upward inside the rail 20, and the lower portion of upper surface of the slide member 24 is pressed against the lower surface of the inward flange 20b of the rail 20, whereby the coupling 21 or 22 is fixed to the rail 20. A washer 27 is interposed between the lower surface of the coupling 21 or 22 and the upper surface of the rail 20, with the higher portion of upper surface of the slide member 24 in contact with the lower surface of the washer 27. A screw insertion hole 28 formed in the coupling 21 or 22 has a stepped portion 28a. A cylindrical spacer 29 having a flange 29a at its upper end is fitted around the shank of the screw 26, and a cylindrical elastic member 30 is provided between the flange 29a of the spacer 29 and the stepped portion 28a of the insertion hole 28. To make the screw 26 rotatable from above for attaching the block coupling 21 to the rail 20, a wrench insertion clearance is formed above the midportion of the block coupling 21 between each adjacent pair of fluid controllers 2 to 14.

The slide member 24 in the foregoing embodiment may be an integral piece instead of being divided in two. In this case, the slide member 24 is inserted into the



rail 20 from one of its front and rear ends.

The rail is not limited particularly in shape but can be modified variously. FIG. 4 shows an example.

With reference to the second embodiment shown in the  
 5 drawing, the rail 40 shown is E-shaped in cross section with its open side up. More specifically, the rail comprises a rail body 41 U-shaped in cross section and having inward flanges 41a, and a T-shaped intermediate wall 42 provided in the widthwise midportion thereof and  
 10 dividing the body 41 widthwise thereof. In this case, a pair of opposite slide members 43 are provided which are rectangular parallelepipedal. As in the foregoing embodiment, the slide member is fastened to the rail 40 by being moved upward by a screw member 26 screwed into  
 15 the slide member.

The rails 20, 40 each provide a track for each of the lines A, B and C for moving the coupling member therealong. Instead of these rails 20, 50, a groove 51 or 53 for guiding a slide member 52 or 54 may be formed  
 20 in the upper surface of the base member 1 to provide a track by the groove 51 or 53 as shown in FIG. 5. With reference to the third embodiments shown in FIGS. 5, (a) and (b), the groove 51 in (a) is a dovetail groove having a downwardly enlarged trapezoidal cross section,

105290 2250880

while the groove 53 shown in (b) is an internally enlarged groove having an inverted T-shaped cross section. In the case of (a), the slide member 52 is a block having a downwardly enlarged trapezoidal cross section. The slide member 54 in (b) is in the form of a rectangular parallelepipedal block which can be accommodated in the enlarged portion of the internally enlarged groove 53. In the case of either (a) or (b), the slide member 52 or 54 is moved up by the screw member 26 driven in and pressed against the edge of the grooved portion 51 or 53 defining an opening.

With the fluid control devices of the first to third embodiments, the device is assembled in its entirety by slidably moving the coupling members 21, 22 along the tracks (the rails 20 or 40 or the grooves 51 or 53) to arrange the coupling members in position, and thereafter mounting each of the fluid controllers 2 to 14 generally on corresponding adjacent pair of the coupling members 21, 22. Thus, the device is easy to assemble.

For example when the second line B is to be built with the same construction as the first line A, the couplings 21, 22 required for connecting the fluid controllers 7, 8, 9, 10 to be added are placed on the track 20, 40, 51 or 53 from the front end thereof and

then slidably moved to the specified position along the track, and the fluid controllers are thereafter mounted on the couplings. When the line is fabricated according to the first or second embodiment, the couplings can be  
5 mounted alternatively from above the track. Further if the massflow controller 2, for example, is to be replaced by one which is different in length along the line, the fluid controllers 3 to 14 need not be removed but the coupling members 21, 22 are loosened, then  
10 slidably moved to the required position along the track 20, 50, 51 or 53 and thereafter fixed to the track, followed by installation of the desired fluid controller. During this procedure, the coupling members on the existing line remain attached to the track and  
15 are prevented from slipping off or becoming lost. When an additional unit is to be inserted anew between the fluid controllers, the same procedure as for the replacement of the massflow controller 2 can be performed. In this way, the lines can be modified  
20 easily.

FIGS. 6 to 8 show a fourth embodiment of fluid control device of the invention, which is the same as the first embodiment in the parallel arrangement of the first line A, second line B and spare line C on the base

member 1, and in the arrangements of the fluid  
controllers 2 to 14 on the first and second lines A, B.  
Throughout FIGS. 1 to 8, like parts are designated by  
like reference numerals or symbols and will not be  
5 described repeatedly.

With reference to FIG. 6, block couplings 61 and  
external member connecting couplings 62 at a lower level  
are slightly modified in shape from those of the first  
embodiment. As shown in detail in FIG. 8, a synthetic  
10 resin slide member 63 having rail holding claws 64 is  
fixed with a screw 65 to the lower end of each of the  
couplings 61, 62. A rail 60 is U-shaped in cross  
section and has outward flanges 60a only but no inward  
flanges. The slide member 63 is inverted U-shaped and  
15 is provided at its lower end with the rail holding claws  
64 which face inward and are in engagement with the  
respective outward flanges 60a of the rail 60. The rail  
holding claws 64 have such elasticity as to be openable  
laterally away from each other. In this way, the  
20 couplings 61, 62 are slidable along the rail 60, usually  
prevented from slipping off the rail upward and made  
forcibly removable upward. To prevent the couplings 61,  
62 as assembled from moving forward or rearward, the  
outer member connecting couplings 62 at the inlet and

T06290-229E6360

outlet and the inlet coupling 61A of the massflow controller 2 each have a slide member 63 which is secured to the rail 60.

With reference to FIG. 7, the three rails 60 of the fourth embodiment are connected to one another at their rear ends by a connecting member 66. This prevents variations in the spacing between the rails 60, further precluding the rails 60 from backlash and the components from slipping off from the rails 60.

According to the fourth embodiment, the rails 60 are not limited specifically in shape but can be altered variously. Although the rails 60 are different from those of the first embodiment in shape, the same rails 20 as in the first embodiment are of course usable. Also usable are a rail 70 and a slide member 71 which are so shaped as shown in FIG. 9.

With the fifth embodiment shown in FIG. 9, the rail 70 is U-shaped in cross section, has inward flanges 70a only but has no outward flanges. The slide member 71 is provided with outward rail holding claws 72 engageable with the respective inward flanges 70a of the rail 70. The rail holding claws 72 have such elasticity as to be deformable inward toward each other. In this way, couplings 61, 62 are slidable along the rail 70, usually

TOP SECRET

prevented from slipping off upward and made forcibly removable upward.

Although made of synthetic resin, the slide members 63, 71 of the fourth and fifth embodiments may alternatively be those made of metal and given such elasticity as to be openable laterally in opposite directions.

The slide member may be made of a metal and so shaped as shown in FIG. 10 (sixth embodiment). With reference to this drawing, the rail 60 and the coupling 61, 61A or 62 used are the same as those of the fourth embodiment. The slide member 81 is inverted U-shaped and provided with inward rail holding claws 82 at its lower end. The slide member 81 is mounted on the rail 60 from one of the front and rear ends thereof, moved to the required position and then fixed with screw members 26. The screw members 26 are screwed into vertical internally threaded portions extending through the slide member 81, tightened up against the outward flanges 60a of the rail 60, with a washer 83 interposed between the member 81 and rail flanges 60a, whereby the couplings 61, 61A or 62 is prevented from moving. The screw insertion holes 28 formed in the coupling 61, 61A or 62 each have a stepped portion 28a as in the first

embodiment, whereas neither the spacer 29 nor the elastic member 30 is used.

The slide member 81 of the sixth embodiment is usable in combination with the slide member 63 of the fourth embodiment. More specifically, the slide members for the outer member connecting couplings 62 at the inlet and outlet and for the inlet coupling 61A of the massflow controller 2 are those 81 of the sixth embodiment, and the other slide members are those 63 of the fourth embodiment. The couplings assembled into the device are then prevented from moving forward or rearward, while the coupling 61 provided with the slide member 63 of the fourth embodiment is removable upward without being moved to the end of the rail 60. This ensures facilitated modification of the lines or addition of lines.

With the fluid control devices of the fourth to sixth embodiments, the device is assembled in its entirety by slidably moving the coupling members 61, 62 along the tracks (rails 60 or 70) to arrange the coupling members in position, and thereafter mounting each of the fluid controllers 2 to 14 generally on two of the coupling members 61, 62. Thus, the device is easy to assemble.

For example when the second line B is to be built with the same construction as the first line A, the couplings 61, 62 required for connecting the fluid controllers 7, 8, 9, 10 to be added are placed on the track 60 or 70 from the front end thereof and then slidingly moved to the specified position along the track, and the fluid controllers are thereafter mounted on the couplings. When the line is fabricated according to the fourth or fifth embodiment, the slide members 63 or 71 can be mounted alternatively from above the track. Additional units or components can be inserted between the fluid controllers similarly, and the lines can be modified easily.

According to the first, second, fourth, fifth and sixth embodiments, each track is provided by a rail 20, 40, 60 or 70 removably mounted on the base member, so that the device can be assembled in its entirety by attaching to the base member 1 the rails each having coupling members 21, 22 or 61, 62 and fluid controllers 2 to 14 mounted thereon, hence easy assembly. Lines can be modified by a procedure comprising removing channel connecting means upward as required, thereafter removing the old line to be modified as mounted on the rail, mounting the rail of a substitute line on the base



member, and finally installing channel connecting means as required for the modification. Similarly, lines can be added merely by removing channel connecting means upward as required, thereafter mounting on the base member the line to be added as mounted on a rail, and finally installing channel connecting means required for the additional installation. Lines can therefore be added or modified with ease.

The base member 1 is in the form of a plate according to the foregoing embodiments, whereas the base member may be in the form of a frame as seen in FIGS. 11 to 13.

With reference to the seventh embodiments shown in these drawings, a base member 91 comprises an inlet-side rail 92, outlet-side rail 93, connecting members 94 interconnecting the two rails 92, 93, and an intermediate rail 95 provided between intermediate portions of the rails 92, 93. Coupling members 21, 22 at a lower level are mounted on a line supporting rail 96 for each of lines A, B. Each of fluid controllers 2 to 14 at a higher level is mounted generally on the corresponding adjacent pair of these couplings 21, 22.

As shown in FIG. 13, the line supporting rail 96 of the present embodiment for each of the lines A, B

20        A shape member of the two-groove type obtained by joining two shape members 97 of the single-groove type is used as it is for the inlet-side rail 92, outlet-side rail 93 and intermediate rail 95. The same shape member 97 of the single-groove type as used for providing the

line supporting rail 96 is used for the connecting members 94 interconnecting the inlet-side rail 92 and the outlet-side rail 93.

The line supporting rail 96 is attached to the rails 5 92, 93 in the same manner as when the coupling member 21 or 22 is attached to the rail 96. Stated more specifically, the line supporting rail 96 has front and rear end portions which are prepared by spot facing. Screw members 100 inserted respectively through these 10 end portions are screwed in slide members 98 provided in the inlet-side and outlet-side rails 92, 93, whereby the line supporting rail 96 is made slidable in a direction (left-right direction) orthogonal to the line (front-rear direction).

15 The connecting member 94 is connected to the inlet-side rail 92, the outlet-side rail 93 and the intermediate rail 95 by the same means as above and is thereby made slidable on these rails 92, 93, 95.

FIGS. 15 and 16 show a modification of the seventh 20 embodiment, i.e., eighth embodiment. With reference to these drawings, a line supporting rail 101 of the embodiment is provided by a two-groove shape member which comprises two shape members 97 of the single-groove type as joined together. The rail 101 has inside

thereof two grooves 101a each having a downwardly tapered trapezoidal cross section. In conformity with this cross section, a slide member 102 also has a downwardly tapered trapezoidal cross section. The slide member 102 has incorporated therein a plunger 103 biased downward by a spring 104. The plunger 103 bears on the bottom face of the grooved portion 101a, whereby the slide member 102 is pushed upward. Accordingly, the slide member 102 is temporarily held in place before a screw 26 is screwed into a vertical internally threaded portion 105 of the slide member 102.

When lines are to be modified or added according to the seventh or eighth embodiment, it is possible to slidably move the line supporting rails 96 or 101 of the existing lines A, B as required, mount the rail of the line to be substituted or added on the base member 91, and thereafter slidably return the rails 96 or 101 of the existing lines A, B to the proper position. Thus, lines can be added or modified with greater ease.

FIG. 17 shows a ninth embodiment. With reference to the drawing, a line supporting rail 111 is provided by a two-groove shaped member. The rail 111 has inside thereof two internally enlarged grooves 111a each opened upward and having a downwardly tapered trapezoidal cross

section. The rail 111 further has a groove 111b formed in each of opposite outer side walls and extending longitudinally of the rail (front-rear direction). A slide member 112 is made of a metal and of the gripping type. Stated more specifically, the slide member 112 is inverted U-shaped and has a top wall 112a and front and rear vertical walls 112b. The slide member 112 is attached to the rail 111 by the opposite vertical walls 112b holding the outer side walls of the rail 111 therebetween. The vertical walls 112b of the slide member 112 are each cut out at an intermediate portion thereof and are thereby given increased elasticity in the left-right direction. Each wall 112b is inwardly bent at an intermediate portion of its height to thereby form an inward protrusion 113. The protrusions 113 of the vertical walls 112b of the slide member 112 are fitted in the grooves 111b in the outer side walls of the rail 111, whereby the slide member 112 is made movable only in the lengthwise direction. A plate spacer 114 is interposed between the upper surface of the rail 111 and the top wall 112b of the slide member 112. Screws 26 extending through the coupling 22 further extend through the top wall 112b of the slide member 112 and have their lower ends screwed in

[illegible]

	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)	(21)	(22)	(23)	(24)	(25)	(26)	(27)	(28)	(29)	(30)	(31)	(32)	(33)	(34)	(35)	(36)	(37)	(38)	(39)	(40)	(41)	(42)	(43)	(44)	(45)	(46)	(47)	(48)	(49)	(50)	(51)	(52)	(53)	(54)	(55)	(56)	(57)	(58)	(59)	(60)	(61)	(62)	(63)	(64)	(65)	(66)	(67)	(68)	(69)	(70)	(71)	(72)	(73)	(74)	(75)	(76)	(77)	(78)	(79)	(80)	(81)	(82)	(83)	(84)	(85)	(86)	(87)	(88)	(89)	(90)	(91)	(92)	(93)	(94)	(95)	(96)	(97)	(98)	(99)	(100)
--	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------

[illegible]

while the metal slid member is more preferably coated with Teflon or the like and thereby given improved slidability.

FIG. 19 shows an eleventh embodiment. With reference to the drawing, a line supporting rail 111 has the same shape as that of the ninth embodiment, while a slide member 131 is adapted to fit into the internally enlarged grooves 111a of the rail 111. More specifically, the slide member 131 is made of rubber and comprises a plate portion 133 in contact with the lower surface of a coupling 22, and downward projections 134 extending downward from the plate portion 133. Each downward projection 134 has a lower end fitted in the enlarged groove 111a so as not to slip out therefrom and is provided with a hollow portion so as to be easily deformable in the leftward or rightward direction. A plate spacer 132 is interposed between the upper surface of the rail 111 and the plate portion 133 of the slide member 131. The spacer 132 has a rectangular hole 135 for inserting the downward projections 134 of the slide member 112 therethrough from above, two circular holes 136 for inserting screws 137 therethrough from below, and downward projections 138 slidably fitted in the rail 111. The slide member 131 is connected to the coupling

22 by fixing the spacer 132 to the coupling 22 with the screws 137. The slide member 131 may of course be made from metal or synthetic resin instead of rubber.

In the fourth embodiment shown in FIG. 8, fifth  
 5 embodiment shown in FIG. 9, ninth embodiment shown in FIG. 17, tenth embodiment shown in FIG. 18 and eleventh embodiment shown in FIG. 19, the slide member 63, 71, 112, 122 or 131 is not fixed with a screw, is therefore movable and is preferably used in combination with a  
 10 slide member fixed to the rail with a screw (e.g., the member 102 of FIG. 15). In this case, the coupling 61, 61A or 22 having the movable slide member 63, 71, 112, 122 or 131 is connected to the coupling 22 having the fixed slide member 102 by the fluid controller and is  
 15 thereby prevented from moving.

When lines are to be modified or added according to the seventh to eleventh embodiments, it is possible to slidably move the line supporting rails 96 or 101 of the existing lines A, B as required, mount the rail of  
 20 the line to be substituted or added on the base member 91, and thereafter slidably return the rails 96 or 101 of the existing lines A, B to the proper position.

Thus, lines can be added or modified with greater ease.

When lines are to be modified or added according to



[illegible]